

# LogTag®

## Products & Features Matrix

	Key: Sensor: I = Internal E = External* Battery: F = Fixed R = Replaceable Alarm Settings: P = Preset C = Configurable	Main Features			Usage		Memory			Connectivity			Other Features			
		Temperature Measurement Range	Sensor	Battery	Multi-Use	Single-Use	~4,000 Logs Memory	~8,000 Logs Memory	~16,000 Logs Memory	Cradle Required	USB Connector	Wifi Connectivity	Auto PDF Output	Display	Audible Alarm	Alarm Settings
<b>Temperature Data Loggers</b>		<b>Product Model</b>														
Temperature Logger	TRIX-8	-40° to +85° C	I	F	✓			✓		✓					C	✓
High Memory Temperature Logger	TRIX-16	-40° to +85° C	I	F	✓				✓						C	
Temperature Logger with External Probe*	TREX-8	-40° to +99° C	E	F	✓				✓						C	
Single-Use Temperature Logger	SRIC-4	-30° to +60° C	I	F		✓	✓			✓					C	
Logger with 30 day display + Fixed Battery	TRID30-7F	-30° to +60° C	I	F	✓			✓		✓			✓		C	
Logger with 30 day display + Replaceable Battery	TRID30-7R	-30° to +60° C	I	R	✓			✓		✓			✓		C	
WHO PQS listed Logger for vaccines	VaxTag	-30° to +60° C	I	F	✓			✓		✓			✓		P	✓
Logger with 30 day display + External Probe*	TRED30-16R	-40° to +99° C	E	R	✓				✓	✓			✓	✓	C	
<b>USB Temperature Data Loggers</b>																
Temperature Logger	USRIC-4	-30° to +60° C	I	F		✓	✓				✓				C	
PDF Logger	USRIC-8	-30° to +60° C	I	F		✓		✓			✓		✓		C	
PDF High Memory Logger	UTRIX-16	-30° to +70° C	I	F	✓				✓		✓		✓		C	
PDF Logger with display + Fixed Battery	UTRID-16	-30° to +60° C	I	F	✓					✓		✓	✓		C	✓
PDF Logger with display + Replaceable Battery	UTRID-16R	-30° to +60° C	I	R	✓					✓		✓	✓		C	
PDF Logger with display & External Probe*	UTRED-16F	-40° to +99° C	E	F	✓					✓		✓	✓		C	
PDF Single-Use Logger with display	USRID-16	-30° to +60° C	I	F		✓				✓		✓	✓		C	
WHO PQS Listed PDF Logger with display	USRID-16W (1 / 2)	-30° to +60° C	I	F		✓				✓		✓	✓		P	✓
Logger with Large display & External Probe*	UTRED30-16	-40° to +99° C	E	R	✓					✓		✓	✓	✓	C	
<b>Wifi Temperature Data Loggers</b>																
WiFi logger with large display & External Probe*	UTRED30-WIFI	-40° to +99° C	E	R	✓			✓		✓	✓	✓	✓	✓	C	
Low Temp WiFi logger with large display & Ext. Probe*	UTREL30-WIFI	-90° to +40° C	E	R	✓				✓		✓	✓	✓	✓	C	

\* Extra Charges Apply For Probes & Accessories



LogTag dataloggers are named using the naming conventions below. Please note that these features may not be accurate, so please to check the product specifications before purchase.

- T** Temperature
- R** Recording
- I** Internal Sensor
- X** Extended Temp Range
- S** Single Use
- C** Commercial Temp Range  
(-30°C to +60°C)
- D** Display
- U** USB
- E** External Sensor
- L** Low Temperature

- H** Humidity
- F** Fixed Battery
- R** Replaceable Battery
- W** WHO-PQS Listed
- 4** ~4,000 Log Memory
- 7** ~7,000 Log Memory
- 8** ~8,000 Log Memory
- 16** ~16,000 Log Memory
- 20** 20-Day Display
- 30** 30-Day Display
- WIFI** WiFi Enabled

